

# **UPGRADABLE HIGH SECURITY READER**

RFID MIFARE® DESFIRE® EV2 & EV3 CARDS, NFC SMARTPHONES



Vandal-proof and extremely scalable, the Architect<sup>®</sup> card reader is specially designed for all your high-security access control applications.

### **WELCOME TO HIGH SECURITY**

The reader uses the latest MIFARE® DESFire® EV2 & EV3 contactless chip technologies with new data security mechanisms:

- Secure Messaging EV2: secure transaction method based on AES-128 with protection against interleaving and replay attacks.
- **Proximity Check:** improved protection against relay attacks.

All public encryption algorithms can be used (3DES, AES, RSA, SHA, etc.), which are recommended by official data security agencies (such as the French national agency ANSSI).

# **ULTIMATE SELF-PROTECTION**

The patented motion sensor pull detection system protects sensitive data by allowing authentication keys to be erased.

Unlike existing solutions within this market, the reliability of the accelerometer avoids potential system bypass.

### CREATE YOUR OWN SCALABLE CONFIGURATION

The Architect<sup>®</sup> reader can be tailored to your needs, ensuring that all functionalities and security levels can be upgraded across all your readers - by RFID card or protocol.

The scalability allows you to implement new functionality such as a touch screen/keypad, QR Code or biometric module.

## OPEN TECHNOLOGIES FOR EASY INTEGRATION

The reader is compatible with all access control systems and accepts multiple interfaces and protocols (Wiegand, Clock&Data, SSCP<sup>®</sup> and OSDP<sup>m</sup>).

# STANDING THE TEST OF TIME

Architect<sup>®</sup> design reader makes it very robust in harsh environments (IP65) with high levels of resistance to vandalism (certified IK10).

## **OUR SECURITY OFFERINGS**

- Easyline: readers and cards pre-configured and programmed, ready to use.
- Expert line: you program your readers and cards in perfect autonomy with the intuitive configuration tools.
- Individual line: we offer a wide range of Premium services to configure and customize your readers and credentials according to your needs.

Find out more



#### DESIGNED & MADE IN FRANCE

# WE'VE GOT YOUR BACK

# 



# **SPECIFICATIONS**

Operating frequency / Standards	13.56 MHz: ISO14443 types A & B, ISO18092	
Chip compatibility	MIFARE® Ultralight® & Ultralight® C, MIFARE® Classic & Classic EV1, MIFARE Plus® (S/X) & Plus® EV1, MIFARE® DESFire® 256, EV1, EV2 & EV3, NFC (HCE), PicoPass® (CSN only), iCLASS™ (CSN only*)	
Functions	CSN, pre-configured (Easyline - PC2) or secure (file, sector) read only / Controlled by protocol (read-write)	
Communication interfaces & protocols	TTL Clock&Data (ISO2) or Wiegand output (encrypted communication option - S31) / RS232 & RS485 outputs (encrypted option - S33) with SSCP® v1 & v2 secure communication protocols; OSDP™ v1 (plain) and v2 (Secure Channel Protocol)	
Decoder compatibility	Compatible with EasySecure (encrypted communication) and "transparent" interfaces: EasyRemote, RemoteSecure & RemoteSecure addressable (4 readers)	
Reading distances**	Up to 8 cm / 3.15" with a MIFARE® DESFire® EV2 or Classic card	
Light indicators	2 RGB LEDs - 360 colors 🔺 🔺 👗 Configuration by RFID card, software or external command (0V) according to the interface	
Audio indicator	Internal buzzer Configuration by RFID card, software or external command (0V) according to the interface	
Power requirement	130 mA/12 VDC max	
Power supply	7 to 28 VDC	
Connections	10-pin plug-in connector (5 mm / 0.2") / 2-pin plug-in connector (5 mm / 0.2"): O/C contact - Tamper detection signal	
Material	ABS-PC UL-V0 (black) / ASA-PC-UL-V0 UV (white)	
Dimensions (h x w x d)	106.6 x 80 x 25.7 mm / 4.21" x 3.15" x 1.02" (general tolerance following ISO NFT 58-000 standard)	
Operating temperatures	- 30°C to + 70°C / - 22°F to + 158°F	
Tamper switch	Accelerometer-based tamper detection system with key deletion option (patented solution) and/or message to the controller	
Protection / Resistance	IP65 - Weather-resistant with waterproof electronics compliant with CEI NF EN 61086 standard Humidity: 0 - 95% / Reinforced vandal-proof structure IK10 certified	
Mounting	Compatible with any surfaces and metal walls - Wall mount/Flush mount: - European 60 & 62 mm / 2.36" & 2.44" - American (metal/plastic) - 83.3 mm / 3.27" - Dimensions: 101.6 x 53.8 x 57.15 mm / 3.98" x 2.09" x 2.24" - Examples: Hubbel-Raco 674, Carlon B120A-UP	
Certifications ( € FC 🚇 🕬 us	CE (Europe), FCC (USA), IC (Canada) and UL	
Part numbers y: case color (1: black - 2 white)	Read-only serial number - TTL Pre-configured read-only Easyline - Wiegand Secure read-only - TTL Secure read-only - RS232 Secure read-only - RS232 Secure read-only - RS485 Secure read-only - EasySecure - RS485 Secure read-only - Secure Plus - RS485 Secure read-only - Secure Plus - RS485 Secure read-only - Secure Plus / EasySecure - RS485 Secure read-only - EasyRemote - RS485 Secure read-only - EasyRemote - RS485 Controlled by SSCP® v1 protocol - RS232 Controlled by SSCP® v1 protocol / RemoteSecure interface - RS485 Controlled by SSCP® v1 protocol / RemoteSecure addressable interface - RS485 Controlled by SSCP® v2 protocol - RS485	ARC-R31-A/PC2-xx/ ARC-R31-A/PH5-xx/ ARC-R31-A/PH5-xx/ ARC-R32-A/PH5-5AB/ ARC-R33-A/PH5-7AB/ ARC-R33-A/PH5-7AB/ ARC-S33-A/PH5-7AB/ ARC-S33-A/PH5-7BB/ ARC-W33-A/PH5-7BB/ ARC-W33-A/PH5-7AB/ ARC-W33-A/PH5-7BB/ ARC-W33-A/PH5-7BB/ ARC-W33-A/PH5-7BC/ ARC-W33-A/PH5-7BC/ ARC-W33-A/PH5-7BC/

# DISCOVER OUR CREDENTIALS AND OUR ERGONOMIC MANAGEMENT TOOLS



13.56 MHz ISO cards & key holders



NFC smartphones using STid Mobile ID® application



Decorative plate / Shield / Spacers / Converter cables / Bio and 125 kHz modules...



SECard configuration kit and SSCP, SSCP2 & OSDP™ protocols

\*Our readers only read the iCLASS<sup>™</sup> chip serial number / UID PICO1444-3B. They do not read iCLASS<sup>™</sup> cryptographic protection or the HID Global serial number / UID PICO 15693. \*\*Caution: information about the distance of communication: measured from the center of the antenna, depending on the type of identifier, size of the identifier, operating environment of the reader, temperatures, power supply voltage and reading functions (secure reading).

Legal statements: STid, SSCP<sup>®</sup> and Architect<sup>®</sup> are trademarks of STid SAS. QR Code is registered trademark of DENSO WAVE INCORPORATED. All other trademarks are property of their respective owners. This document is the exclusive property of STid. STid reserves the right to stop any product or service for any reason and without any liability - Noncontractual photographs.

Headquarters / EMEA

13850 Gréasque, France Tel.: +33 (0)4 42 12 60 60

PARIS-IDF

92290 Châtenay-Malabry, France Tel.: +33 (0)1 43 50 11 43 STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK Tel.: +44 (0) 192 621 7884

NORTH AMERICA

Irving, Texas 75063-2670, USA Tel.: +1 469 524 3442 LATINO AMERICA

San Rafael 06470 CDMX, México Tel.: +52 (55) 5256 4706

# info@stid.com w.stid-security.com