

C20-DN Series Analog Day/Night Camera

1/3-INCH CCD, 650 TVL WITH HIGH SENSITIVITY, TRUE DAY/NIGHT (ICR)

Product Features

- 650 TV Lines
- High Sensitivity
- True Day/Night with Automatic or Manual Control
- 1/3-Inch Format CCD Imager
- Digital Signal Processing
- CS Lens Mount
- Autosensing DC Drive Auto Iris
- Automatic/Manual White Balance Settings for Difficult Lighting Situations
- Selectable Automatic Gain Control
- Advanced Backlight Compensation
- Autosensing Power (24 VAC/12 VDC with Internal Synchronization)
- 2D Digital Noise Reduction (DNR)
- Privacy Zones
- Motion Detection

The **C20-DN Series** is Pelco's digital true day/night CCD camera. Its day/night technology provides outstanding performance over a wide range of lighting conditions. The camera uses a removable infrared (IR) cut filter to switch between color and black-white (B-W) modes as environmental lighting conditions change and the need for infrared sensitivity is realized.

The **C20-DN Series** is an ultra high resolution digital camera with 650 TVL of resolution and 0.13 lux minimum illumination. Camera features include autosensing power (24 VAC or 12 VDC with internal synchronization) and automatic gain control (AGC). The **C20-DN Series** also includes automatic white balance (AWB) for difficult lighting situations, digital noise reduction that minimizes environment noise level, and backlight compensation (BLC) that adjusts the picture to prevent objects from appearing dark due to a strong backlight.



C20-DN
(LENS NOT SUPPLIED WITH CAMERA)

- Built-in Unshielded Twisted Pair (UTP) Output
- Camera Titles
- Adaptive Tone Reproduction (ATR) to Compensate for Gradation of Subjects to an Optimum Level

The **C20-DN Series** also features built-in analytical capabilities including privacy zones, motion detection, and camera titles. These features are easily set using the on-screen menus.

The convenient on-screen menus contains features that are not typically found in a general purpose camera including area masking, titling, pixel correction, and preset lighting profiles.

The **C20-DN Series** is quick and easy to instal. The camera is also featured in Pelco's DomePak® and ImagePak® fixed camera dome/ enclosure packages. The optional C10-UM wall/ceiling/rail mount kit offers easy installation in many nonenclosure applications, for all models.

The **C20-DN Series** has a standard CS lens mount and can be used with fixed, manual, or auto iris (DC drive) lenses. The iris is controlled through a standard 4-pin square connector that is included on all Pelco auto iris lenses.



by Schneider Electric



C3901 / REVISED 6-15-12

TECHNICAL SPECIFICATIONS

MODELS

C20-DN-6X	1/3-inch CCD high resolution day/night camera, 24 VAC or 12 VDC, PAL format
C20-DN-7X	1/3-inch CCD high resolution day/night camera, 220 VAC, PAL format

GENERAL

Imaging Device	Sony® 1/3-Inch EXview HAD CCD II™ 960H
Signal Processing	Sony new digital signal processor, Effio-E™
Day/Night Operation	
Day	Infrared (IR) cut filter
Night	BK-7 glass, same optical displacement as day mode
Picture Elements	976 (H) x 582 (V), approx. 570k
Sensing Area	8.33 mm (1/3 inch) 4.7 x 3.5 mm (3/16 x 1/8-inch)
Scanning System	625 lines, 2:1 interlace
Synchronization System	Internal
Horizontal Resolution	650 TV lines
Auto Iris Lens Type	DC drive
Sensitivity	
Color	0.13 lux, f/1.2, 30 IRE
Mono	0.05 lux, f/1.2, 30 IRE
Signal-to-Noise Ratio	48 dB (>52 dB by parameter adjustment)
Automatic Gain Control	On/off 35 dB
Backlight Compensation	Yes
White Balance	ATW/push lock/manual/anti-CR/user2/ user/push
Color Correction	With white balance
Gamma	Selectable (ATR)
Video Output	1 Vp-p, 75 ohms
Auto White Balance Range	2,500° to 9,500°K
Noise Reduction (DNR)	2D
Privacy Zones	Yes
Motion Detection	Yes
Camera Titles	Yes

ELECTRICAL

Power Requirement	
C20-DN-6X	12 VDC/24 VAC +10% to -15%, 50 Hz
C20-DN-7X	220 VAC +10% to -15%, 50 Hz
Power Consumption	
C20-DN-6X	4 W
C20-DN-7X	5 W
Power Connector	2-pin terminal block with push lock, or line cord on 220 VAC models
Video Connector	BNC
Auto Iris Connector	4-pin connector (miniature square)

MECHANICAL

Lens Mount	CS mount
Camera Mount	1/4-inch UNC-20 screw, top or bottom of camera housing

ENVIRONMENTAL

Operating Temperature	-10° to 50°C (14° to 122°F)
Storage Temperature	-20° to 60°C (-4° to 140°F)
Operating Humidity	20% to 90%, noncondensing
Storage Humidity	20% to 90%, noncondensing

PHYSICAL

Dimensions (includes BNC)	108 x 60 x 55 mm (4.25" L x 2.36" W x 2.17" H)
Weight (without lens)	
C20-DN-6X	0.30 kg (0.66 lb)
C20-DN-7X	0.45 kg (0.99 lb)
Shipping Weight	
C20-DN-6X	0.55 kg (1.21 lb)
C20-DN-7X	0.60 kg (1.32 lb)

CERTIFICATIONS

- CE, Class B
- FCC, Class B
- UL/cUL Listed

RECOMMENDED MOUNTS

C10-UM	C10 series universal wall/ceiling/rail mount kit
--------	--

RECOMMENDED POWER SUPPLIES

TF2000	Power supply for one 24 VAC camera, 20 VA
MCS Series	Multiple 24 VAC camera power supply, indoor
WCS Series	Single/multiple 24 VAC camera power supply, outdoor

RECOMMENDED LENSES

13VA/13VD Series	Varifocal lenses, 1/3-inch format; 13VA (manual iris); 13VD (auto iris, DD)
13ZD Series	Motorized zoom lenses, 1/3-inch format (auto iris, DD)

Pelco by Schneider Electric

3500 Pelco Way, Clovis, California 93612-5699 United States

USA & Canada Tel (800) 289-9100 Fax (800) 289-9150

International Tel +1 (559) 292-1981 Fax +1 (559) 348-1120

www.pelco.com

Pelco, the Pelco logo, and other trademarks associated with Pelco products referred to in this publication are trademarks of Pelco, Inc. or its affiliates. All other product names and services are the property of their respective companies. Product specifications and availability are subject to change without notice. ©Copyright 2012, Pelco, Inc. All rights reserved.