

## 1.3 Megapixel Varifocal Day/Night IP Vandal-proof **Outdoor Dome Camera**

Experience Up to 720p Full HD Video Resolution





## **FEATURES**

- 1/3 in progressive scan CMOS image sensor
- High resolution video up to 1280 x 1024 @ 30 fps, 1280 x 720 (720p) @ 30 fps
- H.264/MJPEG dual codec video streaming
- True day/night (ICR) to capture sharp, detailed images day and night
- Enhanced imaging with 2D + 3D DNR and WDR
- Sens-up automatically enhances DSS to produce brighter images in low light conditions
- Dynamic profile streaming (3 main streams + 4 regions of interest) brings multi-camera capabilities and custom views to a single camera
- LG Ipsolute mobile app (Android + iPhone) available
- ONVIF and PSIA compliant
- IP66 weather rated
- Micro SD card slot for on-board storage

## **SPECIFICATIONS**

Camera

Image Sensor Scanning Mode Resolution Effective Pixels Minimum Illumination

Day/Night Wide Dynamic Range Electronic Shutter (sec) Gain Control White Balance Mode Sense-up (DSS) Noise Reduction IR Sensitivity Pan Angle Tilt Angle

Lens Type Lens Zoom Ratio Focal Length Iris

Horizontal Viewing F-number Angle

Video

Video Compression Format Codec Streaming Capability

Maximum Frame Rate Bit Rate Bit Rate Mode

Audio Audio Compression Format

Features Motion Detection Event Notification Privacy Mask 1/3" CMOS

1/3" CMOS
Progressive Scan
Up to 1280 x 1024
Approx. 1.3 Megapixel
Color: 0.3 Lux @ F1.2
B/W: 0.005 Lux @ F1.2
ICR (Auto/Day/Night)
80dB
1/30 to 1/10000
Auto
Auto (ATW, AWC Push), Manual
Yes

Yes 2D+3D DNR 700 - 1100 nm 0° ~ 360° 0° ~ 75°

Varifocal 3.6x 2.8 - 10mm

H.264 (High Profile Supported), MJPEG

n.zo4 (riigh Profile Supported), MJPEG Dynamic Profile Streaming (up to 7), ROI Streaming 30 fps @ 1280 x 1024, 30 fps @ 720p 256 kbps to 10,240 kbps CBR, VBR

Two-way G.711, G.726

Yes Relay Out, Email, FTP

Analog Video Output Audio Input Audio Output Sensor Input Alarm Ouput SD Card Slot

Network

Interface

Security Number of Connections

General

Power Requirements Power Requirements
Power Consumption
Weight
Dimensions (in.)
Operating Temperature
Storage Temperature
Operating Humidity
Color / Material
Approvals

Operating System

Processor Memory Web Browser

System Requirements

Video Analytics

Ethernet

RJ-45 10/10 1x RCA Out 1x In 1x Out 1x In 1x Out 1x Micro SD

RJ-45 10/100 BASE-T

IPv4/6 - TCP/IP, UDP, HTTP, HTTPS, RTP, RTSP, DHCP, ICMP, IPv4 - FTP, SMTP, NTP, ARP, SNMP v1/v2c/v3, DDNS (LG) Password Protection, HTTPS (SSL, TLS) Up to 10

Intelligent Motion Detection, Streaming Metadata, Trip Zone, Object Counting

PoE / DC12V 5.9 W 1.34 lbs 1.34 lbs 5.51 (Ø) x 4.72 (H) 14°F ~ 122°F -4°F ~ 140°F 0% ~ 80%RH White / Plastic UL, FCC, CE, KCC, Gongan

Windows XP Professional, Windows VISTA, Windows 7

Windows / Intel Core 2 Quad Q6700 (2.66 GHz) or above 2 GB or above RAM Microsoft Internet Explorer 7.0 or above

CD ROM (User's Guide, IP Utility, LG Ipsolute VMS Suite)

Installation Manual Mounting Hardware