

# Compact Color Camera VBC-255 Series

[www.boschsecurity.com](http://www.boschsecurity.com)



**BOSCH**

Invented for life



Advantage Line

The VBC-255 is a compact, rugged, 1/3-inch image format digital color CCD camera. The superior sensitivity, 570 TVL resolution and picture quality provide optimal performance in virtually all situations. The lens wizard automatically detects the lens and allows the installer to easily adjust the lens level and focus without special tools or filters. Automatic black level enhances contrast by removing veiling glare from the picture. NightSense is used to further extend the excellent sensitivity by a factor of 3 in monochrome operation. This fully automatic camera is ready to operate, and is easy to install.

## Features

- ▶ Superior picture quality
- ▶ Excellent resolution (570 TVL sensor resolution)
- ▶ Extended sensitivity with NightSense
- ▶ Auto detection of lens
- ▶ Easy to install

## 2 | Compact Color Camera VBC-255 Series

### Technical specifications

Electrical			
Model No.	Rated Voltage		Range
VBC-255-11 (C)	12 VDC	10.8-39 VDC	
	24 VAC 50 Hz	12-28 VAC 45-65 Hz	
VBC-255-51 (C)	230 VAC 50 Hz	85-265 VAC 45-65 Hz	
Power Consumption	4 W, excluding lens		
Imager	Interline transfer CCD, 1/3-inch image format		
Active Pixels	752 H x 582 V		
Horizontal Resolution	570 TVL Sensor Resolution		
Signal-to-Noise Ratio	50 dB		
Gain	21 dB, (max)		
Electronic Shutter	Automatic, 1/50 to 1/125000 sec.		
Aperture Correction	Horizontal and vertical, symmetrical		
Backlight Compensation	Center window weighting		
White Balance	Automatic sensing (2500–9000 K)		
Remote Control	Bilinx coaxial communication		
Video Output	Composite video 1.0 Vpp, 75 Ohm		
Line-Lock synchronization (AC only)	Synchronizes the camera to the power line zero crossing for roll-free vertical interval switching. Vertical phase delay can be adjusted (0-358 degrees) to allow vertical synchronization in multi-phase power installations.		
Free running synchronization (DC-supply or L/L off)	Internal crystal reference is standard on all models.		
Sensitivity			
(3200 k)			
	Usable Picture (30 IRE)	Usable Picture (50 IRE)	Full Video
Scene Illumination <sup>1)</sup> (color mode)	0.30 lux (0.03 fc)	0.65 lux (0.07 fc)	2.6 lux (0.26 fc)
Imager Illumination (color mode)	0.045 lux (0.005 fc)	0.10 lux (0.010 fc)	0.40 lux (0.040 fc)
Scene Illumination <sup>1)</sup> (night mode)	0.12 lux (0.012 fc)	0.26 lux (0.026 fc)	1.04 lux (0.104 fc)
Imager Illumination (night mode)	0.018 lux (0.002 fc)	0.040 lux (0.004 fc)	0.16 lux (0.016 fc)
Mechanical			
Dimensions (H x W x D)	58 x 66 x 122 mm (2.28 x 2.6 x 4.8 in.) including connectors		
Weight	0.45 kg (0.99 lb)		
Connectors	Video Output: BNC Video/DC-iris connector: 4-pin EIA-J		
Camera Mounting	Top and Bottom, 1/4-inch 20 UNC		
Lens Mounting	C and CS		
Environmental			
Operating Temperature	-20°C to 50°C (-4°F to 122°F)		
Storage Temperature	-25°C to 70°C (-13°F to 158°F)		
Operating Humidity	5% to 93% non-condensing		
Power			

#### Represented by:

##### Americas:

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

##### Europe, Middle East, Africa:

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

##### Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

##### China:

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

##### America Latina:

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com

Power connector (VBC-255-11, VBC-255-11C)	Push type connectors, polarity independent, isolated from video output terminals
Power connector (VBC-255-51)	2-wire power cord with Euro plug
Power connector (VBC-255-51C)	2-wire power cord with Chinese plug



#### Notice

Lens is not included

Certifications and approvals	
Region	Certification
Europe	CE
Standards	
	FCC Part 15, Class B
	EN55022: Class B
	EN50130-4
	EN60065
Ordering information	
VBC-255-11 Compact Color Camera, 12 VDC/24 VAC	VBC-255-11
VBC-255-11C Compact Color Camera, 12 VDC/24 VAC, China	VBC-255-11C
VBC-255-51 Compact Color Camera, 230 VAC	VBC-255-51
VBC-255-51C Compact Color Camera, 230 VAC, China	VBC-255-51C